

70mm Rehau 706

Product Specification

Casement Windows

Characteristics

- 70mm depth White 52mm even leg outer frame profile has bevelled edges for more attractive appearance
- Fully welded and grooved corners, mullions and transoms
- Internal decorative Ovalo bead with as standard
- Concealed drainage

Locking Systems - Maco Shootbolt

Combination locking incorporating a range of mushroom cams

Night vent position as standard, providing both ventilation and security

- Adjustable cams for handle pressure

Security Hinge System

- Friction stay hinges with hinge arm locating securely into corner keeps

White Cranked Handles

- Automatic locking with push-to-release
- Keyed Locking cylinder lock

Glazing

- 28mm Low-Emissivity Sealed Unit - Silver Spacer

Cill

- 155mm White Cill included in all height measurements

Gaskets

- Black low level gasket

Product Idiosyncrasies

- Minimum transom drop is 370mm
- Maximum side hung are 675mm x 1350mm
- Maximum top hung is 1250mm x 1250mm

Maximum Entrance Door 1050mm x 2200mm
Maximum French Door 1800mm x 2200mm

Residential Doors

70mm White Door system 75mm Even leg outer frame

- White Handles/lever-lever
- Latest generation multi-point door lock with 10 year guarantee
- Triple high security hooks bi-directional throw for anti-jemmy and two roller cams
- Adjustable Flag Hinges
- Generous adjustment on rollers and keeps
- French door features double handle set / working slave
- Cylinder lock with 3 keys 6 pin anti-pick/anti-drill

Glazing

- 28mm Toughened Low-Emissivity Sealed Units - Silver Spacer

Cills

- 155mm included in all height measurements

Gaskets

- Black low level gasket

Conditions of Sale

All widths and heights include cills and add-ons
Points denote hinge

All products viewed from the outside

S denotes Slave on French doors

Arrow denotes direction of slider

Acknowledgements are signed as acceptance

Optional Extras when Requested

Egress fire non lock handle (600mm sash)

- Face drainage
- 85mm Stub Cills
- 180mm Cills
- Coloured Spacer Bars
- Georgian Bars
- Sloped Beads
- Handles - Chrome (silver) or Gold
- Green Blanks for Escape handles
- Trickle Vents—2000mm or 4000mm
- Restrictor Hinges

- Low PVCu threshold—52mm
- Aluminium threshold—26mm
Gold or Silver
- Door restrictor—open out
- Sidescreens and toplights
- Heavy Outer Frame
- Thumb-turn
- Lever pad door handles

Profile Options

Mahogany
Mahogany on White
Golden Oak
Golden Oak on White

Add-Ons

- 15mm
- 45mm
- 3mm In-line Coupler
- 20mm Flush Reinforced Coupler