

DECEUNINCK Feature Sash

Product Specification

Casement Windows

Characteristics

- 70mm depth White 55mm even leg outer frame profile has feature edge for more attractive appearance
- Fully welded and grooved corners, mullions and transoms
- Internal decorative Ogee bead as standard
- Concealed drainage

Locking Systems - Maco Shootbolt

Combination locking incorporating a range of mushroom cams

Night vent position as standard, providing both ventilation and security

- Adjustable cams for handle pressure

Security Hinge System

- Friction stay hinges with hinge arm locating securely into corner keeps

White Cranked Handles

- Automatic locking with push-to-release
- Keyed Locking cylinder lock

Glazing

- 28mm Low-Emissivity Sealed Unit - Silver Spacer

Cill

- 150mm White Cill included in all height measurements

Gaskets

- Grey low level gasket

Product Idiosyncrasies

- Minimum transom drop is 350mm
- Maximum side hung are 675mm x 1350mm
- Maximum top hung is 1250mm x 1250mm

Maximum Entrance Door 1050mm x 2200mm
Maximum French Door 1800mm x 2200mm

Residential Doors

70mm White Door system 70mm even leg outer frame

- White Handles/lever-lever
- Latest generation multi-point door lock with 10 year guarantee
- Triple high security hooks bi-directional throw for anti - jemmy and two roller cams
- Adjustable Butt Hinges
- Generous adjustment on rollers and keeps
- French door features double handle set with top & bottom corner drivers
- Cylinder lock with 3 keys 6 pin anti-pick/anti-drill

Glazing

- 28mm Toughened Low-Emissivity Sealed Units - Silver Spacer

Cills

- 150mm included in all height measurements

Gaskets

- Grey low level gasket

Conditions of Sale

All widths and heights include cills and add-ons

Points denote hinge

All products viewed from the outside

S denotes Slave on French doors

Arrow denotes direction of slider

Acknowledgements are signed as acceptance

Optional Extras when Requested

- Egress fire green push button non lock handle (600mm sash)
- Face drainage
- 85mm Stub Cills
- 180mm Cills
- 250mm Cills (white only)
- Coloured Spacer Bars
- Georgian Bars
- Handles—Chrome, Gold or Black
- Trickle Vents—2000mm or 4000mm
- Restrictor Hinges
- Low PVCu threshold—55mm
- Aluminium threshold—19mm Gold or silver
- Door restrictor—open out
- Sidescreens and toplight
- Heavy Outer Frame 70mm
- Thumb-turn
- Lever/Lever split spindle door handles

Profile Options

Rosewood - Black Gaskets
Rosewood on White - Black/Grey Gaskets
Oak - Black Gaskets
Oak on White - Black/Grey Gaskets
White Ash - Grey Gaskets

Add-Ons

- 15mm
- 25mm
- 40mm
- 70mm
- 2mm Coupler
- 5.5mm Aluminium Coupler
- 24mm Aluminium Structural Coupler
- 55mm Aluminium Structural Coupler